

DECLARATION OF PERFORMANCE

NL Stopprofiel
FR Profilé d'arrêt
DE Abschlussprofil
EN Stop Bead

Art. Nr. **1006 2,6**

DoP-Nr.: **WIL200026000**



EN 13658-1

Binnenbepiestering
Enduit intérieur
Innenputz
Inside plastering



45/10/5 rvh 11+5 ev 35

<http://www.wilmar.be/dop>

Material : DX 51D AZ-150 0,4mm

Initial inspection by origin EN 10215 / 10143

Mechanical traits (average) :

Yield (MPA) Re	331
Tensile (MPA) Rm	389
Elongation (%)	30

Chemical traits (average) :

C	0,05
Mn	0,19
Si	0,01
P	0,09
S	0,005
Al	0,048

Weight/pc 0,457 kg	Pc/Pack 10	Size/Pack 45x35x2600	Weight/Pack 4,576 kg	Pack/Pal 350	Size/Pal 880x1020x2600	Weight/Pal 1601,6 kg
-----------------------	---------------	-------------------------	-------------------------	-----------------	---------------------------	-------------------------

Declared performance

length	2600	mm
width	45 x 6 x 5	mm
thickness	0,405	mm
weight	0,176	kg/m not perforated
aluzinc coating	19,6	µm / side a
	19,3	µm / side b
aluzinc weight	150	kg/m

Authorized representative : CEO	Date	1/07/2013	Signed : Tom Heyvaert	Tom Heyvaert Waalstrand 13 B -9080 Lochristi
---------------------------------	------	-----------	-----------------------------	--